NSN 5910-01-089-1976

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-089-1976 **Body Style:** Flat pack **Reliability Indicator:** Not established **Mounting Slot Width:** 0.562 inches **Body Length:** 29.500 inches **Body Width:** 6.000 inches **Body Height:** 20.800 inches **Center To Center Distance Between Terminals Parallel To Length:** 9.000 inches **Terminal Diameter:** 0.500 inches **Terminal Height From Body:** 6.560 inches **Unthreaded Mounting Hole Diameter:** 0.562 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 19.120 inches **Schematic Diagram Designator:** No common or grounded electrode (s) Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 7.120 inches **Mounting Facility Screw Thread Series Designator: Mounting Facility Type And Quantity:** 2 mounting slots and 2 threaded mounting studs and 4 unthreaded mounting holes **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 3.500 microfarads single section

Nonderated Operating Temp:

Between 15.6 degrees celsius and 38.0 degrees celsius

Thread Size:

0.500 inches

Nonderated Continuous Voltage Rating And Type Per Section:

33000.0 dc single section

Tolerance Range Per Section:

-0.00/+20.00 percent single section

NSN 5910-01-089-1976

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Case Material:
Metal
Terminal Type And Quantity:
2 standoff, threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A010b0