

View Online at <https://aerobasegroup.com/nsn/5910-01-089-9619>

Body Style:

W/o mtg facilities, terminal (s) on one end

Reliability Indicator:

Not established

Terminal Length:

Between 0.032 inches and 0.094 inches

Body Diameter:

Between 2.469 inches and 2.547 inches

Body Length:

Between 4.078 inches and 4.250 inches

Center To Center Distance Between Terminals Parallel To Diameter:

Between 1.000 inches and 1.250 inches

Terminal Diameter:

0.190 inches

Center To Center Distance Between Mounting Facilities Parallel To Diameter:

Between 1.000 inches and 1.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Anode Type:

Etched foil

Impedance At Minimum Operating Temperature In Ohms:

0.015

Electrical Polarization:

Polarized

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

2 threaded mounting holes

Capacitance Value Per Section:

65000.000 microfarads single section

Nonderated Operating Temp:

85.0 degrees celsius

Thread Size:

0.190 inches

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Tolerance Range Per Section:

-10.00/+100.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Equivalent Series Resistance At Reference Temperature In Ohms:

0.022

Dc Leakage At Reference Temp:

6.000 microamperes

Case Insulation Material:

Plastic

Terminal Type And Quantity:

2 threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0