NSN 5910-01-092-1696

Mica Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-092-1696 **Thread Class:** 2a **Body Style:** Compression **Terminal Length:** 0.281 inches **Bushing Diameter:** 0.250 inches **Bushing Length:** 0.500 inches **Body Length:** 0.938 inches **Body Width:** 0.875 inches **Body Height:** 0.860 inches **Dissipation Factor At 25 Deg Celsius In Percent:** 0.0040 **Mounting Facility Screw Thread Series Designator:** Uns **Inclosure Type:** Encased **Bushing Shape:** Round Insulation Dc Resistance At 25 Deg Celsius: 100.0 gigohms **Mounting Facility Type And Quantity:** 1 threaded bushing Thready Qty Per Inch (tpi): 40 **Nonderated Operating Temp:** Between -35.0 degrees celsius and 85.0 degrees celsius **Thread Size:** 0.250 inches Capacitance Range In Picofarads: +780.0/+2110.0 single section

Nonderated Voltage Rating And Type:

250.0 dc continuous single section

Adjustment Device Drive Type And Quantity:

1 slotted screw

Terminal Type And Quantity:

2 tab, solder lug

NSN 5910-01-092-1696

Mica Dielectric Variable Capacitor - Page 2 of 2



| Shelf L | ₋ife: |
|---------|-------|
|---------|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0