## NSN 5910-01-092-3403

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-092-3403 **Body Style:** W/o mtg facilities, terminal (s) on one end **Reliability Indicator:** Not established **Terminal Length:** 1.625 inches **Body Diameter:** 0.150 inches **Body Length:** 0.250 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.120 inches **Terminal Diameter:** 0.016 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 2.200 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 15.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 6.0000 Dc Leakage At Reference Temp: 1.500 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:** 

**Plastic** 

## NSN 5910-01-092-3403

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type A	and Quantity	<b>/</b> :
-----------------	--------------	------------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0