Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-094-2176

#### Unable To Decode:

W/mtg tabs/flanges, terminals on opposite surfaces

#### **Reliability Indicator:**

Not established

### **Terminal Length:**

2.250 inches

#### Body Length:

17.125 inches

#### Body Width:

9.310 inches

**Body Height:** 

#### 4.950 inches

**Terminal Diameter:** 

#### 0.250 inches

Unthreaded Mounting Hole Diameter:

### 0.221 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

6.750 inches

### Schematic Diagram Designator:

No common or grounded electrode (s)

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

10.310 inches

### Mounting Facility Type And Quantity:

4 unthreaded mounting holes

### Features Provided:

Hermetically sealed case

### Capacitance Value Per Section:

0.125 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

88000.0 dc single section

### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### Case Material:

Metal

## Insulation Resistance At Reference Temp:

390.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.000

### **Dielectric Material:**

Plastic



### Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0