Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-094-4318

### **Body Style:**

W/o mtg facilities, axial terminals

### **Reliability Indicator:**

Not established

## **Terminal Length:**

2.000 inches

#### **Body Diameter:**

0.687 inches

#### **Body Length:**

1.687 inches

#### **Terminal Diameter:**

0.032 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

#### Impedance At Minimum Operating Tempurature In Ohms:

135.0

#### **Electrical Polarization:**

Polarized

#### **Capacitance Value Per Section:**

27.000 microfarads single section

## Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

300.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+50.00 percent single section

#### **Case Material:**

Metal

**Capacitive Electrode Material:** 

Aluminum

#### **Dissipation Factor At Reference Tempurature In Percent:**

12.0000

# **Terminal Surface Treatment:**

Solder

# **Case Insulation Material:**

Plastic

# **Test Data Document:**

81349-mil-c-62 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

# **Specification Data:**

81349-mil-c-62/2 government specification

# NSN 5910-01-094-4318

Electrolytic Fixed Capacitor - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0

