## NSN 5910-01-094-5891

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-094-5891

Body	Style:
------	--------

W/mtg bracket, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

Between 1.625 inches and 2.625 inches

**Body Diameter:** 

Between 0.995 inches and 1.015 inches

**Body Length:** 

Between 2.094 inches and 2.156 inches

**Terminal Diameter:** 

0.040 inches

**Unthreaded Mounting Hole Diameter:** 

0.156 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Mounting Facility Type And Quantity:** 

1 unthreaded mounting holes

**Features Provided:** 

Hermetically sealed case

**Capacitance Value Per Section:** 

2.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

400.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

50000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

0.300

**Terminal Surface Treatment:** 

Solder

**Dielectric Material:** 

Plastic

**Terminal Type And Quantity:** 

2 uninsulated wire lead

Shelf Life:

N/a

## NSN 5910-01-094-5891

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	nit	O+	Measure:
u		v	wicasuic.

--

Demilitarization:

No

Fiig:

A010b0