Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-095-0708

#### **Body Style:**

W/o mtg facilities, terminal (s) on one end

### **Reliability Indicator:**

Not established

### **Terminal Length:**

1.000 inches

### **Body Diameter:**

0.500 inches

#### **Body Length:**

1.790 inches

#### Center To Center Distance Between Terminals Parallel To Diameter:

0.200 inches

#### **Terminal Diameter:**

0.032 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

### **Electrical Polarization:**

Polarized

#### **Capacitance Value Per Section:**

820.000 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 105.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+100.00 percent single section

### **Case Material:**

Metal

#### **Capacitive Electrode Material:**

Aluminum

### Equivalent Series Resistance At Reference Tempurature In Ohms:

0.21

## Dc Leakage At Reference Temp:

4.000 microamperes

## **Case Insulation Material:**

Plastic

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

## Unit Of Measure:

--

Electrolytic Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0