## NSN 5910-01-096-3088

**Body Style:** 

Established

1.0000

**Reliability Indicator:** 

**Terminal Length:** 

1.625 inches **Body Diameter:** 

W/o mtg facilities, axial terminals

Reliability Failure Rate Level In Percent:

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-096-3088

0.312 inches				
Body Length:				
0.887 inches				
Terminal Diameter:				
0.025 inches				
Schematic Diagram Designator:				
No common or grounded electrode (s)				
Features Provided:				
Hermetically sealed case				
Capacitance Value Per Section:				
0.470 microfarads single section				
Nonderated Operating Temp:				
Between -65.0 degrees celsius and 100.0 degrees celsius				
Nonderated Continuous Voltage Rating And Type Per Section:				
22.0 ac-rms single section and 30.0 dc single section				
Tolerance Range Per Section:				
-1.00/+1.00 percent single section				
Case Material:				
Metal				
Insulation Resistance At Reference Temp:				
100000.0 megohms				
Dissipation Factor At Reference Tempurature In Percent:				
0.1500				
Case Insulation Material:				
Plastic				
Test Data Document:				
81349-mil-c-83421/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification				
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain				
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).				
Terminal Type And Quantity:				
2 uninsulated wire lead				
Shelf Life:				
N/a				
Unit Of Measure:				
<del></del>				

## NSN 5910-01-096-3088

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



	atio	

No

Fiig:

A010b0