

View Online at <https://aerobasegroup.com/nsn/5910-01-096-7982>

**Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:**

Not established

**Terminal Length:**

2.000 inches

**Body Diameter:**

0.375 inches

**Body Length:**

1.375 inches

**Schematic Diagram Designator:**

Electrod (s) grounded to case, w/gnd terminal

**Electrical Polarization:**

Polarized

**End Application:**

Helicopter, uscg search and rescue, hh-60j; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; helicopter, mh-53e; aircraft, viking s-3b; aircraft, hawkeye e-2c; helicopter, carrier based asw, sh-60f; helicopter, seasprite h-2; aircraft, tomcat f-14

**Capacitance Value Per Section:**

400.000 microfarads single section

**Nonderated Operating Temp:**

Between -40.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

10.0 dc single section

**Criticality Code Justification:**

Feat

**Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:**

Metal

**Capacitive Electrode Material:**

Aluminum

**Terminal Surface Treatment:**

Solder

**Case Insulation Material:**

Plastic

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

2 uninsulated wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A010b0