

View Online at <https://aerobasegroup.com/nsn/5910-01-096-7982>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

2.000 inches

Body Diameter:

0.375 inches

Body Length:

1.375 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Electrical Polarization:

Polarized

End Application:

Helicopter, uscg search and rescue, hh-60j; helicopter, advance attack, ah-1w; helicopter, search and rescue, hh-60h; helicopter, mh-53e; aircraft, viking s-3b; aircraft, hawkeye e-2c; helicopter, carrier based asw, sh-60f; helicopter, seasprite h-2; aircraft, tomcat f-14

Capacitance Value Per Section:

400.000 microfarads single section

Nonderated Operating Temp:

Between -40.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

10.0 dc single section

Criticality Code Justification:

Feat

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Aluminum

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

Special Features:

Weapon system essential

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A010b0