

View Online at <https://aerobasegroup.com/nsn/5910-01-097-2758>

Body Style:

Dual inline

Reliability Indicator:

Not established

Body Length:

Between 0.840 inches and 0.860 inches

Body Width:

Between 0.290 inches and 0.310 inches

Body Height:

0.275 inches

Center To Center Distance Between Terminals Parallel To Length:

0.700 inches

Center To Center Distance Between Terminals Parallel To Width:

0.350 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Anode Type:

Solid

Electrical Polarization:

Polarized

Section Quantity:

4

Capacitance Value Per Section:

6.800 microfarads all sections

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

10.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

35.0 dc all sections

Tolerance Range Per Section:

-20.00/+20.00 percent all sections

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

6.0000

Dc Leakage At Reference Temp:

6.000 microamperes

Terminal Type And Quantity:

16 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0