NSN 5910-01-099-8739

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-099-8739 **Body Style:** Rotary **Terminal Length:** 0.110 inches **Overall Height:** 0.315 inches **Overall Diameter:** 0.335 inches Tempurature Coefficient Of Capacitance In Ppm Per Deg Celsius: -1400.0 single section **Tolerance Of Tempurature Coefficient In Ppm Per Deg Celsius:** -800.0/+800.0 single section **Center To Center Distance Between Terminals Parallel To Diameter:** 0.295 inches Center To Center Distance Between Mounting Facilities Parallel To Diameter: 0.295 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Terminal Width:** 0.040 inches **Terminal Thickness:** 0.015 inches **Inclosure Type:** Encased **Terminal Location:** Circumference 90 degrees apart on end opposite adjustment control perpendicular **Adjustment Device Torque:** Between 0.300 inch-ounces and 3.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10000.0 megohms **Mounting Facility Type And Quantity: Nonderated Operating Temp:** Between -20.0 degrees celsius and 85.0 degrees celsius Capacitance Range In Picofarads: +5.0/+50.0 single section **Nonderated Voltage Rating And Type:** 250.0 dc continuous single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Terminal Type And Quantity:**

2 printed circuit

NSN 5910-01-099-8739

Ceramic Dielectric Variable Capacitor - Page 2 of 2



Shelf	Life:
N/a	

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A096a0