NSN 5910-01-100-5739

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-100-5739 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.750 inches **Body Diameter:** 0.390 inches **Body Length:** 2.812 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Impedance At Minimum Operating Tempurature In Ohms:** 25.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 30.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 95.0 degrees celsius Dc Leakage At Maximum Operating Temp: 30.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 150.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 4.00 Dc Leakage At Reference Temp: 10.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-100-5739

Electrolytic Fixed Capacitor - Page 2 of 2



Shel	fli	fo.
Olici		ıc.

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0