## NSN 5910-01-101-2278

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-101-2278

Body Style:
W/o mtg facilities, terminals on opposite surfaces
Reliability Indicator:
Not established
Terminal Length:
1.500 inches
Body Length:
0.530 inches
Body Width:
0.200 inches
Body Height:
0.320 inches
Terminal Diameter:
0.020 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.100 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section
200.0 dc single section
200.0 dc single section  Tolerance Range Per Section:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic  Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life:
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a
200.0 dc single section  Tolerance Range Per Section: -1.00/+1.00 percent single section  Case Material: Plastic Insulation Resistance At Reference Temp: 25000.0 megohm-microfarads  Dissipation Factor At Reference Tempurature In Percent: 0.5000  Terminal Surface Treatment: Solder  Terminal Type And Quantity: 2 uninsulated wire lead  Shelf Life: N/a

Fiig: A010b0