

View Online at https://aerobasegroup.com/nsn/5910-01-101-3355

## **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

0.0010

**Terminal Length:** 

1.625 inches

**Body Diameter:** 

0.700 inches

**Body Length:** 

1.875 inches

**Terminal Diameter:** 

0.040 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### Capacitance Value Per Section:

22.000 microfarads single section

## Nonderated Operating Temp:

Between -65.0 degrees celsius and 100.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

30.0 dc single section

#### **Tolerance Range Per Section:**

-5.00/+5.00 percent single section

**Case Material:** 

Metal

## **Dissipation Factor At Reference Tempurature In Percent:**

0.1500

**Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

Plastic

# Test Data Document:

81349-mil-c-83421 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Terminal Type And Quantity:**

2 uninsulated wire lead

#### **Specification Data:**

81349-mil-c-83421/1 government specification

Shelf Life:

N/a

- Unit Of Measure:
- ---



Demilitarization:

No

Fiig:

A010b0