## NSN 5910-01-102-2133



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-102-2133 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 2.500 inches **Body Diameter:** 0.937 inches **Body Length:** 3.843 inches **Terminal Diameter:** 0.040 inches **Schematic Diagram Designator:** Two common terminals for each electrode **Impedance At Minimum Operating Tempurature In Ohms:** 0.156 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 250.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 105.0 degrees celsius **Dc Leakage At Maximum Operating Temp:** 750.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section **Tolerance Range Per Section:** -10.00/+50.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Equivalent Series Resistance At Reference Tempurature In Ohms:** 0.52 Dc Leakage At Reference Temp:

125.000 microamperes **Terminal Surface Treatment:** 

Solder

**Case Insulation Material:** 

**Plastic** 

**Terminal Type And Quantity:** 

4 uninsulated wire lead

## NSN 5910-01-102-2133

Electrolytic Fixed Capacitor - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0