NSN 5910-01-103-2279

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-103-2279

| Rody | Style: | |
|------|--------|--|
| Dogv | OLVIC. | |

W/o mtg facilities terminal (s) on one surface

Reliability Indicator:

Not established

Terminal Length:

Between 1.625 inches and 1.850 inches

Body Length:

Between 0.285 inches and 0.295 inches

Body Width:

Between 0.315 inches and 0.325 inches

Body Height:

Between 0.140 inches and 0.150 inches

Center To Center Distance Between Terminals Parallel To Length:

Between 0.190 inches and 0.210 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

5000.0 megohms

Capacitance Value Per Section:

0.100 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-5.00/+5.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

500000.0 megohms

Dissipation Factor At Reference Tempurature In Percent:

0.300

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5910-01-103-2279

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | tariz | |
|--|-------|--|
| | | |
| | | |

No

Fiig:

A010b0