

View Online at https://aerobasegroup.com/nsn/5910-01-104-0598

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Not established

**Terminal Length:** 

1.250 inches

**Body Diameter:** 

Between 0.080 inches and 0.100 inches

### **Body Length:**

Between 0.230 inches and 0.250 inches

**Terminal Diameter:** 

0.016 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

470.000 picofarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-10.0/+2.0 without voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

100000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# Test Data Document:

81349-mil-c-11015/25 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A010b0