Plastic Dielectric Fixed Capacitor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5910-01-104-6809

## **Body Style:**

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.750 inches

Body Length:

1.812 inches

**Body Width:** 

1.062 inches

**Body Height:** 

2.250 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

Capacitance Value Per Section:

0.500 microfarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

1000.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

1.0000

# Test Data Document:

81349-mil-c-19978/3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0