

View Online at <https://aerobasegroup.com/nsn/5910-01-104-7215>

**Body Style:**

Flat pack

**Reliability Indicator:**

Established

**Terminal Length:**

0.110 inches

**Body Length:**

0.320 inches

**Anode Type:**

Solid

**End Application:**

Kg-66

**Features Provided:**

Hermetically sealed case

**Capacitance Value Per Section:**

10.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Nonderated Continuous Voltage Rating And Type Per Section:**

15.0 dc single section

**Capacitive Electrode Material:**

Tantalum

**Terminal Surface Treatment:**

Solder

**Special Features:**

Selected item

**Test Data Document:**

81349-mil-c-55365/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 98230-0n288743 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

2 tab, solder lug

**Specification Or Standard:**

Cwr03 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0