

View Online at <https://aerobasegroup.com/nsn/5910-01-104-7215>

Body Style:

Flat pack

Reliability Indicator:

Established

Terminal Length:

0.110 inches

Body Length:

0.320 inches

Anode Type:

Solid

End Application:

Kg-66

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

10.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

15.0 dc single section

Capacitive Electrode Material:

Tantalum

Terminal Surface Treatment:

Solder

Special Features:

Selected item

Test Data Document:

81349-mil-c-55365/2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). And 98230-0n288743 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

2 tab, solder lug

Specification Or Standard:

Cwr03 style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0