NSN 5910-01-105-3455

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-105-3455

Body Style:	
W/o mtg facilities, terminals on opposite surfaces	
Mil-std-1276 Wire Lead Type Designator:	
N-1	
Reliability Indicator:	
Not established	
Terminal Length:	
1.250 inches	
Body Length:	
0.425 inches	
Body Width:	
0.120 inches	
Body Height:	
0.170 inches	
Terminal Diameter:	
0.016 inches	
Schematic Diagram Designator:	
No common or grounded electrode (s)	
Capacitance Value Per Section:	
0.068 microfarads single section	
William Town and an Italia Book and a La Book at Constitution Office	
Voltage Tempurature Limits Per Section In Percent Capacitance Change) :
-15.0/+15.0 without voltage applied single section	e :
	€:
-15.0/+15.0 without voltage applied single section	:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp:	e:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius	e:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section:	e:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section	:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section:	:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section	9:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material:	9:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic	=:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:	> :
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads	= :
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:	:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000	:
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Type And Quantity:	::
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Type And Quantity: 2 uninsulated wire lead	::
-15.0/+15.0 without voltage applied single section Nonderated Operating Temp: Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 200.0 dc single section Tolerance Range Per Section: -5.00/+5.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 1.0000 Terminal Type And Quantity: 2 uninsulated wire lead Shelf Life:	::

No

Demilitarization:

NSN 5910-01-105-3455

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0