

View Online at https://aerobasegroup.com/nsn/5910-01-105-4795

### **Body Style:**

W/thd mtg bushing, terminals on opposite ends

**Reliability Indicator:** 

Not established

## Width Across Flats:

0.312 inches

#### **Terminal Length:**

0.234 inches

**Body Length:** 

0.500 inches

### Schematic Diagram Designator:

Feedthrough

### Mounting Facility Screw Thread Series Designator:

Unef

### Mounting Facility Type And Quantity:

1 threaded bushing

#### **Capacitance Value Per Section:**

10.000 picofarads single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

## Thread Size:

0.250 inches

## Nonderated Continuous Voltage Rating And Type Per Section:

500.0 dc single section

#### **Tolerance Range Per Section:**

-20.00/+20.00 percent single section

### **Case Material:**

Metal

Insulation Resistance At Reference Temp:

100000.0 megohms

#### **Dissipation Factor At Reference Tempurature In Percent:**

2.000

# **Terminal Surface Treatment:**

Solder

# **Precious Material And Location:**

Body surfaces silver

# **Terminal Type And Quantity:**

2 tab, solder lug

Shelf Life:

N/a

# Unit Of Measure:

---



Demilitarization:

No

Fiig:

A010b0