NSN 5910-01-106-4416

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-106-4416

·	
Body Style:	
W/thd mtg hole/stud, terminal (s) on one end	
Reliability Indicator:	
Not established	
Width Across Flats:	
0.250 inches	
Terminal Length:	
0.421 inches	
Body Diameter:	
0.690 inches	
Body Length:	
0.250 inches	
Continuous Current Rating In Amps:	
25.0	
Schematic Diagram Designator:	
Feedthrough	
Mounting Facility Screw Thread Series Designator:	
Unf	
Mounting Facility Type And Quantity:	
1 threaded bushing	
Insulation Resistance At Maximum Operating Temp:	
500.0 megohms	
Capacitance Value Per Section:	
250000.000 picofarads single section	
Nonderated Operating Temp:	
Between 55.0 degrees celsius and 85.0 degrees celsius	
Thread Size:	
0.312 inches	
Nonderated Continuous Voltage Rating And Type Per Section	1:
240.0 ac-rms single section and 450.0 dc single section	
Tolerance Range Per Section:	
-20.00/+80.00 percent single section	
Case Material:	
Plastic	
Insulation Resistance At Reference Temp:	
5000.0 megohms	
Dissipation Factor At Reference Tempurature In Percent:	
3.000	
Terminal Surface Treatment:	
Solder	
Terminal Type And Quantity:	

2 eyelet w/wire lead

NSN 5910-01-106-4416

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0