

View Online at <https://aerobasegroup.com/nsn/5910-01-106-4416>

Body Style:

W/thd mtg hole/stud, terminal (s) on one end

Reliability Indicator:

Not established

Width Across Flats:

0.250 inches

Terminal Length:

0.421 inches

Body Diameter:

0.690 inches

Body Length:

0.250 inches

Continuous Current Rating In Amps:

25.0

Schematic Diagram Designator:

Feedthrough

Mounting Facility Screw Thread Series Designator:

Unf

Mounting Facility Type And Quantity:

1 threaded bushing

Insulation Resistance At Maximum Operating Temp:

500.0 megohms

Capacitance Value Per Section:

250000.000 picofarads single section

Nonderated Operating Temp:

Between 55.0 degrees celsius and 85.0 degrees celsius

Thread Size:

0.312 inches

Nonderated Continuous Voltage Rating And Type Per Section:

240.0 ac-rms single section and 450.0 dc single section

Tolerance Range Per Section:

-20.00/+80.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

5000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

3.000

Terminal Surface Treatment:

Solder

Terminal Type And Quantity:

2 eyelet w/wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0