NSN 5910-01-106-4490

Body Style:

Reliability Indicator:

Not established

Terminal Length:

0.297 inchesBody Diameter:0.562 inchesBody Length:

W/thd mtg studs, axial terminals

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-106-4490

1.125 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 0.625 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Mounting Facility Screw Thread Series Designator:** Unc **Mounting Facility Type And Quantity:** 2 threaded mounting studs **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 0.220 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius **Thread Size:** 0.138 inches Nonderated Continuous Voltage Rating And Type Per Section: 400.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section **Case Material:** Metal **Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Surface Treatment:** Solder **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a

NSN 5910-01-106-4490

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A010b0