## NSN 5910-01-106-6966

Ceramic Dielectric Fixed Capacitor - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5910-01-106-6966              |
|--|
| Body Style:  |
| W/o mtg facilities terminal (s) on one surface                             |
| Reliability Indicator:   |
| Not established  |
| Terminal Length:   |
| 1.250 inches   |
| Body Length:   |
| 0.200 inches   |
| Body Width:  |
| 0.200 inches   |
| Body Height:   |
| 0.125 inches   |
| Center To Center Distance Between Terminals Parallel To Length:            |
| 0.100 inches   |
| Terminal Diameter:   |
| 0.020 inches   |
| Schematic Diagram Designator:  |
| No common or grounded electrode (s)  |
| Capacitance Value Per Section:   |
| 47.000 picofarads single section   |
| Nonderated Operating Temp:   |
| Between -55.0 degrees celsius and 125.0 degrees celsius                    |
| Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius: |
| 0.0 single section   |
| Nonderated Continuous Voltage Rating And Type Per Section:                 |
| 100.0 dc single section  |
| Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:   |
| -30.0/+30.0 single section   |
| Tolerance Range Per Section:   |
| -5.00/+5.00 percent single section   |
| Case Material:   |
| Plastic  |
| Insulation Resistance At Reference Temp:                                   |
| 100000.0 megohms   |
| Dissipation Factor At Reference Tempurature In Percent:                    |
| 0.1000   |
| Terminal Type And Quantity:  |
| 2 uninsulated wire lead  |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

## NSN 5910-01-106-6966

Ceramic Dielectric Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0