

View Online at https://aerobasegroup.com/nsn/5910-01-106-6968

| ody Style: | |
|---|-----|
| Chip type | |
| eliability Indicator: | |
| lot established | |
| ody Length: | |
| .125 inches | |
| ody Width: | |
| .095 inches | |
| ody Height: | |
| .050 inches | |
| chematic Diagram Designator: | |
| lo common or grounded electrode (s) | |
| Capacitance Value Per Section: | |
| 000.000 picofarads single section | |
| londerated Operating Temp: | |
| etween -55.0 degrees celsius and 125.0 degrees celsius | |
| empurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsiu | ıs: |
| .0 single section | |
| londerated Continuous Voltage Rating And Type Per Section: | |
| 0.0 dc single section | |
| olerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: | |
| 30.0/+30.0 single section | |
| olerance Range Per Section: | |
| 10.00/+10.00 percent single section | |
| case Material: | |
| Ceramic | |
| nsulation Resistance At Reference Temp: | |
| 000.0 megohms | |
| issipation Factor At Reference Tempurature In Percent: | |
| .0010 | |
| erminal Type And Quantity: | |
| bonding pad | |
| shelf Life: | |
| l/a | |
| Init Of Measure: | |
| | |
| Demilitarization: | |
| lo | |
| iig: | |
| 010b0 | |