

View Online at <https://aerobasegroup.com/nsn/5910-01-107-3997>

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Established

Reliability Failure Rate Level In Percent:

1.0000

Terminal Length:

1.250 inches

Body Diameter:

Between 0.120 inches and 0.140 inches

Body Length:

Between 0.230 inches and 0.250 inches

Terminal Diameter:

Between 0.015 inches and 0.019 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

Insulation Resistance At Maximum Operating Temp:

10000.0 megohms

Capacitance Value Per Section:

0.022 microfarads single section

Voltage Temperature Limits Per Section In Percent Capacitance Change:

-10.0/+2.0 with rated voltage applied single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

Tolerance Range Per Section:

-10.00/+10.00 percent single section

Case Material:

Plastic

Insulation Resistance At Reference Temp:

100000.0 megohms

Dissipation Factor At Reference Temperature In Percent:

1.0000

Terminal Surface Treatment:

Solder

Test Data Document:

81349-mil-c-39014 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 uninsulated wire lead

Specification Data:

81349-mil-c-39014/21 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0