

View Online at https://aerobasegroup.com/nsn/5910-01-107-7254

Body Style:
Dual inline
Reliability Indicator:
Not established
Terminal Length:
0.165 inches
Body Length:
Between 0.087 inches and 0.095 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
0.135 inches
Center To Center Distance Between Terminals Parallel To Width:
Between 0.300 inches and 0.400 inches
Terminal Diameter:
Between 0.008 inches and 0.015 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
220.000 picofarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
0.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
100.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius: -30.0/+30.0 single section
-30.0/+30.0 single section
-30.0/+30.0 single section Tolerance Range Per Section:
-30.0/+30.0 single section <b>Tolerance Range Per Section:</b> -10.00/+10.00 percent single section
-30.0/+30.0 single section <b>Tolerance Range Per Section:</b> -10.00/+10.00 percent single section <b>Case Material:</b>
-30.0/+30.0 single section <b>Tolerance Range Per Section:</b> -10.00/+10.00 percent single section <b>Case Material:</b> Plastic
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp:
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent:
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000 Quality Factor At Reference Temp:
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000 Quality Factor At Reference Temp: 1000.0000
-30.0/+30.0 single section Tolerance Range Per Section: -10.00/+10.00 percent single section Case Material: Plastic Insulation Resistance At Reference Temp: 1000.0 megohm-microfarads Dissipation Factor At Reference Tempurature In Percent: 0.1000 Quality Factor At Reference Temp: 1000.0000



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0