Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-108-0059

# **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

# **Reliability Failure Rate Level In Percent:**

2.0000

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.289 inches

**Body Length:** 

0.686 inches

**Terminal Diameter:** 

0.025 inches

#### Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

## **Electrical Polarization:**

Polarized

#### **Features Provided:**

Hermetically sealed case

## Capacitance Value Per Section:

100.000 microfarads single section

# Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

## Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

## **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

## Case Material:

Metal

## **Capacitive Electrode Material:**

Tantalum

## **Dissipation Factor At Reference Tempurature In Percent:**

0.0600

## Dc Leakage At Reference Temp:

15.000 microamperes

# **Case Insulation Material:**

Plastic

## **Terminal Type And Quantity:**

2 uninsulated wire lead

## Shelf Life:

N/a

# NSN 5910-01-108-0059

Electrolytic Fixed Capacitor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A010b0