## NSN 5910-01-108-5132

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-108-5132 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** Between 1.250 inches and 1.750 inches **Body Diameter:** Between 0.120 inches and 0.145 inches **Body Length:** 0.422 inches **Terminal Diameter:** 0.020 inches **Schematic Diagram Designator:** Electrod (s) grounded to case, w/gnd terminal **Anode Type:** Solid **Electrical Polarization:** Polarized **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -80.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 6.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 20.0 dc single section **Tolerance Range Per Section:** -20.00/+20.00 percent single section Case Material: Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** Dc Leakage At Reference Temp: 0.500 microamperes **Terminal Surface Treatment:** Solder

**Case Insulation Material:**Plastic

## NSN 5910-01-108-5132

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

2 uninsulated wire lead

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0