NSN 5910-01-108-8063

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-108-8063

Body Style:

W/o mtg facilities, axial terminals

Reliability Indicator:

Not established

Terminal Length:

Between 1.250 inches and 1.750 inches

Body Diameter:

Between 0.279 inches and 0.299 inches

Body Length:

Between 0.655 inches and 0.717 inches

Terminal Diameter:

0.020 inches

Schematic Diagram Designator:

Electrod (s) grounded to case, w/gnd terminal

Anode Type:

Solid

Electrical Polarization:

Polarized

Features Provided:

Hermetically sealed case

Capacitance Value Per Section:

47.000 microfarads single section

Nonderated Operating Temp:

Between -80.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

8.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Metal

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Tempurature In Percent:

6 000

Dc Leakage At Reference Temp:

7.000 microamperes

Terminal Surface Treatment:

Solder

Case Insulation Material:

Plastic

NSN 5910-01-108-8063

Electrolytic Fixed Capacitor - Page 2 of 2



Terminal Type And Quantity	Terminal	Type	And	Quantity	/ :
----------------------------	----------	-------------	-----	----------	------------

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0