

View Online at <https://aerobasegroup.com/nsn/5910-01-109-7483>

**Body Style:**

Dual inline

**Reliability Indicator:**

Not established

**Body Length:**

0.200 inches

**Body Width:**

Between 0.240 inches and 0.280 inches

**Body Height:**

0.180 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.100 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.325 inches and 0.375 inches

**Schematic Diagram Designator:**

Two common terminals for each electrode

**Anode Type:**

Solid

**Electrical Polarization:**

Polarized

**Capacitance Value Per Section:**

15.000 microfarads single section

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Dc Leakage At Maximum Operating Temp:**

10.0 microamperes

**Nonderated Continuous Voltage Rating And Type Per Section:**

20.0 dc single section

**Tolerance Range Per Section:**

-20.00/+20.00 percent single section

**Case Material:**

Plastic

**Capacitive Electrode Material:**

Tantalum

**Dissipation Factor At Reference Temperature In Percent:**

1.0000

**Dc Leakage At Reference Temp:**

6.000 microamperes

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A010b0