

View Online at <https://aerobasegroup.com/nsn/5910-01-109-7483>

Body Style:

Dual inline

Reliability Indicator:

Not established

Body Length:

0.200 inches

Body Width:

Between 0.240 inches and 0.280 inches

Body Height:

0.180 inches

Center To Center Distance Between Terminals Parallel To Length:

0.100 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.325 inches and 0.375 inches

Schematic Diagram Designator:

Two common terminals for each electrode

Anode Type:

Solid

Electrical Polarization:

Polarized

Capacitance Value Per Section:

15.000 microfarads single section

Nonderated Operating Temp:

Between -55.0 degrees celsius and 85.0 degrees celsius

Dc Leakage At Maximum Operating Temp:

10.0 microamperes

Nonderated Continuous Voltage Rating And Type Per Section:

20.0 dc single section

Tolerance Range Per Section:

-20.00/+20.00 percent single section

Case Material:

Plastic

Capacitive Electrode Material:

Tantalum

Dissipation Factor At Reference Temperature In Percent:

1.0000

Dc Leakage At Reference Temp:

6.000 microamperes

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0