NSN 5910-01-110-1904



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-110-1904 **Body Style:** W/o mtg facilities, terminal (s) on one end Reliability Indicator: Not established **Terminal Length:** 0.750 inches **Body Diameter:** 0.440 inches **Body Length:** 0.680 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.200 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Anode Type:** Solid **Impedance At Minimum Operating Tempurature In Ohms:** 8.0 **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 33.000 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section Case Material: **Plastic Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent:** 8.0000

Dc Leakage At Reference Temp: 10.000 microamperes **Terminal Surface Treatment:**

Terminal Type And Quantity:

2 uninsulated wire lead

Solder

NSN 5910-01-110-1904

Electrolytic Fixed Capacitor - Page 2 of 2



_					
C.	~~	14	I i	ife:	
J.	16			HE.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0