NSN 5910-01-111-6702

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-111-6702

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
1.250 inches
Body Length:
0.600 inches
Body Width:
0.375 inches
Body Height:
0.295 inches
Center To Center Distance Between Terminals Parallel To Length:
0.500 inches
Terminal Diameter:
0.025 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Capacitance Value Per Section:
0.0768 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 125.0 degrees celsius
Tempurature Coefficient Of Capacitance Per Section In Ppm Per Deg Celsius:
-200.0 single section
Nonderated Continuous Voltage Rating And Type Per Section:
50.0 dc single section
Tolerance Of Tempurature Coefficient Per Section In Ppm Per Deg Celsius:
-30.0/+30.0 single section
Tolerance Range Per Section:
-1.00/+1.00 percent single section
Case Material:
Case Material: Plastic
Plastic
Plastic Insulation Resistance At Reference Temp:
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.1500
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms Dissipation Factor At Reference Tempurature In Percent:
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Type And Quantity: 2 uninsulated wire lead
Plastic Insulation Resistance At Reference Temp: 1000000.0 megohms Dissipation Factor At Reference Tempurature In Percent: 0.1500 Terminal Type And Quantity:

--

NSN 5910-01-111-6702

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Demilitarization:

No

Fiig:

A010b0