NSN 5910-01-112-4367

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-112-4367 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 1.0000 **Terminal Length:** 1.625 inches **Body Diameter:** 0.400 inches **Body Length:** 1.013 inches **Terminal Diameter:** 0.032 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Features Provided:** Hermetically sealed case **Capacitance Value Per Section:** 2.000 microfarads single section **Nonderated Operating Temp:** Between -65.0 degrees celsius and 100.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 30.0 dc single section **Tolerance Range Per Section:** -1.00/+1.00 percent single section Case Material: Metal **Dissipation Factor At Reference Tempurature In Percent:** 0.1500 **Case Insulation Material:** Plastic **Test Data Document:** 81349-mil-c-83421/1 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 2 uninsulated wire lead Shelf Life:

No

N/a

Unit Of Measure:

Demilitarization:

NSN 5910-01-112-4367

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Fiig:

A010b0