

View Online at <https://aerobasegroup.com/nsn/5910-01-112-6228>

**Body Style:**

Rotary

**Body Diameter:**

0.218 inches

**Body Height:**

0.145 inches

**Temperature Coefficient Of Capacitance In Ppm Per Deg Celsius:**

0.0 single section

**Tolerance Of Temperature Coefficient In Ppm Per Deg Celsius:**

-250.0/+250.0 single section

**Center To Center Distance Between Terminals Parallel To Diameter:**

0.195 inches

**End Application:**

Los angeles class ss (688), aircraft c-2a(reprocured), helicopter mh-53e, radar series an/sps-49(v), landing craft air cushion(lcac) , helicopter search and rescue hh-60h, helicopter carrier based asm sh-60f, helicopter uscg search and rescue hh-60j, helicopter advanced attack ah-1w

**Inclosure Type:**

Encased

**Mounting Facility Type And Quantity:**

2 terminal

**Nonderated Operating Temp:**

Between -55.0 degrees celsius and 85.0 degrees celsius

**Criticality Code Justification:**

Feat

**Capacitance Range In Picofarads:**

+5.0/+30.0 single section

**Nonderated Voltage Rating And Type:**

50.0 dc continuous single section

**Adjustment Device Drive Type And Quantity:**

1 slotted screw

**Special Features:**

Weapons system essential

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A096a0