NSN 5910-01-114-7000



Electrolytic Fixed Capacitor - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5910-01-114-7000 **Body Style:** W/o mtg facilities, axial terminals **Reliability Indicator:** Not established **Terminal Length:** 1.250 inches **Body Diameter:** 0.135 inches **Body Length:** 0.297 inches **Terminal Diameter:** Between 0.019 inches and 0.026 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Electrical Polarization:** Polarized **Capacitance Value Per Section:** 1.000 microfarads single section **Nonderated Operating Temp:** Between -30.0 degrees celsius and 85.0 degrees celsius Dc Leakage At Maximum Operating Temp: 14.0 microamperes Nonderated Continuous Voltage Rating And Type Per Section: 35.0 dc single section **Tolerance Range Per Section:** -5.00/+5.00 percent single section **Case Material:** Metal **Capacitive Electrode Material: Tantalum Dissipation Factor At Reference Tempurature In Percent: Equivalent Series Resistance At Reference Tempurature In Ohms:** 70.80 Dc Leakage At Reference Temp: 2.000 microamperes **Terminal Surface Treatment:** Solder **Case Insulation Material:**

Plastic

Terminal Type And Quantity:

2 uninsulated wire lead

NSN 5910-01-114-7000

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A010b0