NSN 5910-01-114-8238

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-114-8238 **Body Style:** W/o mtg facilities terminal (s) on one surface **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Body Length:** 0.550 inches **Body Width:** 0.400 inches **Body Height:** 0.240 inches Center To Center Distance Between Terminals Parallel To Length: 0.400 inches **Terminal Diameter:** 0.025 inches **Schematic Diagram Designator:** No common or grounded electrode (s) **Insulation Resistance At Maximum Operating Temp:** 1000.0 megohms **Capacitance Value Per Section:** 0.010 microfarads single section **Nonderated Operating Temp:** Between -55.0 degrees celsius and 125.0 degrees celsius Nonderated Continuous Voltage Rating And Type Per Section: 600.0 dc single section **Tolerance Range Per Section:** -10.00/+10.00 percent single section **Case Material: Plastic Insulation Resistance At Reference Temp:** 50000.0 megohms **Dissipation Factor At Reference Tempurature In Percent:** 0.3000 **Terminal Surface Treatment:**

Solder

Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

NSN 5910-01-114-8238

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| _ | | •• | • - | | | | |
|---|----|----|-----|-----|-------------|-----|----|
| 1 | em | | ゖっ | riz | 2 †1 | n | |
| _ | | | ıιa | 114 | au | VII | ١. |

No

Fiig:

A010b0