## NSN 5910-01-115-1589

Plastic Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-115-1589

**Body Style:** 

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

Body Length:

2.500 inches

Body Width:

-

1.188 inches

**Body Height:** 

3.875 inches

**Center To Center Distance Between Terminals Parallel To Length:** 

1.125 inches

**Terminal Height From Body:** 

0.750 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Features Provided:** 

Hermetically sealed case

**Insulation Resistance At Maximum Operating Temp:** 

20.0 megohm-microfarads

**Capacitance Value Per Section:** 

2.000 microfarads single section

**Nonderated Operating Temp:** 

Between -65.0 degrees celsius and 125.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

1500.0 dc single section

**Tolerance Range Per Section:** 

-10.00/+10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

15000.0 megohm-microfarads

**Dissipation Factor At Reference Tempurature In Percent:** 

1.0000

**Terminal Surface Treatment:** 

Solder

**Test Data Document:** 

81349-mil-c-19978 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

2 standoff, solder lug

**Specification Data:** 

81349-mil-c-19978/3 government specification

## NSN 5910-01-115-1589

Plastic Dielectric Fixed Capacitor - Page 2 of 2



Sh	elf	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0