## NSN 5910-01-116-0701

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-116-0701

Body Style:
W/mtg tabs/flanges terminals on opposite surfaces
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.0000054
Terminal Length:
1.313 inches
Body Length:
3.370 inches
Body Width:
7.500 inches
Body Height:
4.870 inches
Continuous Current Rating In Amps:
300.0
Center To Center Distance Between Terminals Parallel To Width:
1.800 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.719 inches
Mounting Facility Type And Quantity:
6 unthreaded mounting holes
Section Quantity:
2
Capacitance Value Per Section:
4.000 microfarads single section
Nonderated Operating Temp:
Between -65.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
440.0 ac-peak all sections
Tolerance Range Per Section:
-1.30/+1.20 microfarads single section
Case Material:
Metal
Case Insulation Material:
Paper
Terminal Type And Quantity:

4 threaded stud

## NSN 5910-01-116-0701

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
B

Demilitarization:

Yes - demil/mli

Fiig:

A010b0