## NSN 5910-01-116-4728

Electrolytic Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-116-4728

Body Style:
W/o mtg facilities terminal (s) on one surface
Reliability Indicator:
Not established
Terminal Length:
Between 1.500 inches and 1.750 inches
Body Length:
0.230 inches
Body Width:
0.310 inches
Body Height:
0.130 inches
Center To Center Distance Between Terminals Parallel To Length:
Between 0.175 inches and 0.225 inches
Terminal Diameter:
Between 0.014 inches and 0.018 inches
Schematic Diagram Designator:
No common or grounded electrode (s)
Electrical Polarization:
Polarized
End Application:
4910-00-124-2554
Capacitance Value Per Section:
22.000 microfarads single section
Nonderated Operating Temp:
Between -55.0 degrees celsius and 85.0 degrees celsius
Nonderated Continuous Voltage Rating And Type Per Section:
15.0 dc single section
Tolerance Range Per Section:
-20.00/+20.00 percent single section
Case Material:
Plastic
Capacitive Electrode Material:
Tantalum
Dissipation Factor At Reference Tempurature In Percent:
6.000
Dc Leakage At Reference Temp:
3.000 microamperes
Terminal Surface Treatment:

Solder

**Terminal Type And Quantity:** 

2 uninsulated wire lead

## NSN 5910-01-116-4728

Electrolytic Fixed Capacitor - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A010b0