Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-116-8214

### Body Style:

W/o mtg facilities terminal (s) on one surface

**Reliability Indicator:** 

Not established

# **Terminal Length:**

0.125 inches

#### **Body Length:**

0.385 inches

#### **Body Width:**

0.225 inches

#### **Body Height:**

#### 0.125 inches

## Center To Center Distance Between Terminals Parallel To Length:

0.300 inches

#### **Terminal Diameter:**

0.020 inches

## Schematic Diagram Designator:

No common or grounded electrode (s)

## **Capacitance Value Per Section:**

0.034 microfarads single section

### Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

### Nonderated Continuous Voltage Rating And Type Per Section:

50.0 dc single section

#### **Tolerance Range Per Section:**

-1.00/+1.00 percent single section

#### **Case Material:**

Plastic

## Insulation Resistance At Reference Temp:

50000.0 megohms

# Dissipation Factor At Reference Tempurature In Percent:

0.5000

# **Terminal Surface Treatment:**

Solder

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No



**Fiig:** A010b0