

View Online at https://aerobasegroup.com/nsn/5910-01-117-6243

### **Body Style:**

W/o mtg facilities, axial terminals

**Reliability Indicator:** 

Established

**Reliability Failure Rate Level In Percent:** 

1.0000

**Terminal Length:** 

1.500 inches

**Body Diameter:** 

0.140 inches

**Body Length:** 

0.390 inches

**Terminal Diameter:** 

0.027 inches

Schematic Diagram Designator:

No common or grounded electrode (s)

#### **Capacitance Value Per Section:**

0.012 microfarads single section

## Voltage Tempurature Limits Per Section In Percent Capacitance Change:

-15.0/+15.0 with rated voltage applied single section

## Nonderated Operating Temp:

Between -55.0 degrees celsius and 125.0 degrees celsius

#### Nonderated Continuous Voltage Rating And Type Per Section:

100.0 dc single section

#### **Tolerance Range Per Section:**

-10.00/+10.00 percent single section

#### **Case Material:**

Ceramic

Insulation Resistance At Reference Temp:

1000.0 megohm-microfarads

Dissipation Factor At Reference Tempurature In Percent:

2.5000

# Test Data Document:

81349-mil-c-39014/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Terminal Type And Quantity:

2 uninsulated wire lead

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

# NSN 5910-01-117-6243

Ceramic Dielectric Fixed Capacitor - Page 2 of 2

**Fiig:** A010b0

