## NSN 5910-01-122-3927

Paper Dielectric Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-122-3927

<b>Body</b>	Stv	٠ ما
DOUV	OLV.	ıe.

W/o mtg facilities, terminal (s) on one surface

**Reliability Indicator:** 

Not established

**Body Length:** 

Between 2.100 inches and 2.280 inches

**Body Width:** 

Between 1.250 inches and 1.370 inches

**Body Height:** 

Between 4.690 inches and 4.870 inches

**Continuous Current Rating In Amps:** 

11.0

Center To Center Distance Between Terminals Parallel To Length:

Between 0.780 inches and 0.840 inches

**Terminal Diameter:** 

0.250 inches

**Terminal Height From Body:** 

Between 0.520 inches and 0.640 inches

**Schematic Diagram Designator:** 

No common or grounded electrode (s)

**Capacitance Value Per Section:** 

5.000 microfarads single section

**Nonderated Operating Temp:** 

Between -55.0 degrees celsius and 75.0 degrees celsius

Nonderated Continuous Voltage Rating And Type Per Section:

600.0 ac-peak single section

**Tolerance Range Per Section:** 

-10.00 to 10.00 percent single section

**Case Material:** 

Metal

Insulation Resistance At Reference Temp:

10000.0 megohms

**Dissipation Factor At Reference Tempurature In Percent:** 

1.000

**Terminal Type And Quantity:** 

2 standoff, threaded stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

## NSN 5910-01-122-3927 Paper Dielectric Fixed Capacitor - Page 2 of 2



Fiig:

A010b0