NSN 5910-01-122-6709

Ceramic Dielectric Variable Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-122-6709 **Body Style:** Rotary **Terminal Length:** 0.262 inches **Body Diameter:** 0.375 inches **Body Height:** 0.275 inches **Center To Center Distance Between Terminals Parallel To Diameter:** 0.387 inches **Terminal Diameter:** 0.040 inches **Quality Factor At 25 Deg Celsius:** 500.0 **Inclosure Type: Encased Adjustment Device Torque:** Between 1.000 inch-ounces and 6.000 inch-ounces Insulation Dc Resistance At 25 Deg Celsius: 10.0 gigohms **Mounting Facility Type And Quantity:** 2 terminal **Nonderated Operating Temp:** Between -55.0 degrees celsius and 85.0 degrees celsius **Capacitance Range In Picofarads:** +2.0/+8.0 single section **Nonderated Voltage Rating And Type:** 350.0 dc continuous single section Capacitance Change In Percent At Operating Tempurature From 25 Deg Celsius: -4.50/+2.00 single section and -2.50/+2.00 single section **Adjustment Device Drive Type And Quantity:** 1 slotted screw **Capacitance Drift In Picofarads:** 0.50 single section **Precious Material And Location:** Metal parts surfaces silver **Precious Material:** Silver **Terminal Type And Quantity:** 2 pin Shelf Life:

N/a

NSN 5910-01-122-6709

Ceramic Dielectric Variable Capacitor - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A096a0