NSN 5910-01-123-0580

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5910-01-123-0580

| Body Style: | | | | |
|--|--|--|--|--|
| W/o mtg facilities, terminals on opposite surfaces | | | | |
| Reliability Indicator: | | | | |
| Not established | | | | |
| Terminal Length: | | | | |
| 2.764 inches | | | | |
| Body Length: | | | | |
| 1.490 inches | | | | |
| Body Width: | | | | |
| 0.964 inches | | | | |
| Body Height: | | | | |
| 1.490 inches | | | | |
| Terminal Diameter: | | | | |
| 0.032 inches | | | | |
| Schematic Diagram Designator: | | | | |
| One terminal common to each section | | | | |
| Section Quantity: | | | | |
| 4 | | | | |
| Features Provided: | | | | |
| Hermetically sealed case | | | | |
| Capacitance Value Per Section: | | | | |
| 1.680 microfarads single section | | | | |
| Nonderated Operating Temp: | | | | |
| Between -55.0 degrees celsius and 105.0 degrees celsius | | | | |
| Nonderated Continuous Voltage Rating And Type Per Section: | | | | |
| 400.0 dc all sections | | | | |
| Tolerance Range Per Section: | | | | |
| -10.00/+10.00 percent all sections | | | | |
| Case Material: | | | | |
| Metal | | | | |
| Insulation Resistance At Reference Temp: | | | | |
| 10000.0 megohm-microfarads | | | | |
| Dissipation Factor At Reference Tempurature In Percent: | | | | |
| 1.000 | | | | |
| Terminal Surface Treatment: | | | | |
| Solder | | | | |
| Terminal Type And Quantity: | | | | |
| 6 uninsulated wire lead | | | | |
| Shelf Life: | | | | |
| N/a | | | | |
| Unit Of Measure: | | | | |

--

NSN 5910-01-123-0580

Paper-plastic Dielectric Metallized Fixed Capacitor - Page 2 of 2



| | atio | |
|--|------|--|
| | | |
| | | |

No

Fiig:

A010b0